Band-stop Filter · 2200–2400 MHz

Insertion loss is at most 3 dB in both passbands, DC–2180 MHz and 2420–5000 MHz. Both connectors are on the same end of the housing.

RF Performance

Parameter	Value
Stopband	2200–2400 MHz
Stopband Rejection	≥50 dB (2200–2400 MHz)
Lower Passband	DC–2180 MHz
Upper Passband	2420–5000 MHz
Passband Insertion Loss	≤3 dB (DC–2180 MHz / 2420–5000 MHz)
Passband VSWR	≤1.8 (DC–2180 MHz / 2420–5000 MHz)

Design Ratings

Parameter	Value
Power Handling	150 W (Guaranteed by design)

Typical series reference data

The N-K and SMA-K configurations share these typical series reference data.

Parameter	S12 (dB)	S11 VSWR
2150 MHz	-0.42	1.23
2180 MHz	-2.48	1.41
2185 MHz	-5.35	4.78
2190 MHz	-12.65	12.51
2195 MHz	-36.71	22.46
2200 MHz	-76.11	36.25
2250 MHz	-76.54	45.2
2300 MHz	-59.65	43.49
2350 MHz	-58.55	41.48
2400 MHz	-66.47	31.26
2405 MHz	-38.45	27.46
2410 MHz	-13.85	13.68
2415 MHz	-6.25	4.48
2420 MHz	-2.47	1.33

Typical series reference data

The N-K and SMA-K configurations share these typical series reference data.

Parameter	S12 (dB)	S11 VSWR
2450 MHz	-0.48	1.16

Mechanical and Interface Specifications

Parameter	Value
RF Connector	N-K
Connector Shell Material	304 stainless steel
RF Impedance	50 Ω
Surface Finish	Black baked paint
Body Length	300 mm
Body Width	72 mm
Housing height from flange underside	<55 mm
Length Between Outer Flange Edges	320 mm
Number of mounting slots	4
Mounting slot width	4.5 mm
Arc-centre spacing within one slot	10 mm
Slot-centre pitch, lengthwise	310 mm
Slot-centre pitch, crosswise	50 mm
Connector Center Spacing	34 mm
RF axis offset from the top edge in side view	10 mm

Handling and Installation

Both RF connectors are on the same end of the housing. Clean the product surface without immersing the product in cleaning fluid. For conditions in which the overall product temperature exceeds 125 °C, consult LCRF before ordering.

Document notice

Specifications are subject to revision. Before design release, confirm the current document revision and product-specific requirements with LCRF. The approved quotation and order documentation define the supplied configuration.