Band-stop Filter · 2300–2370 MHz

Insertion loss is at most 2.5 dB in both passbands, DC–2280 MHz and 2390–6000 MHz. Both connectors are on the same end of the housing.

RF Performance

Parameter	Value
Stopband	2300–2370 MHz
Stopband Rejection	≥60 dB (2300–2370 MHz)
Lower Passband	DC–2280 MHz
Upper Passband	2390–6000 MHz
Passband Insertion Loss	≤2.5 dB (DC–2280 MHz / 2390–6000 MHz)
Passband VSWR	≤1.8 (DC–2280 MHz / 2390–6000 MHz)

Design Ratings

Parameter	Value
Power Handling	150 W (Guaranteed by design)

Typical series reference data

The N-K and SMA-K configurations share these typical series reference data.

Parameter	S12 (dB)	S11 VSWR
2250 MHz	-0.66	1.17
2280 MHz	-1.71	1.39
2285 MHz	-3.07	3.78
2290 MHz	-6.79	10.44
2295 MHz	-26.47	21.97
2300 MHz	-83.46	41.12
2310 MHz	-69.46	41.82
2340 MHz	-68.02	43.19
2360 MHz	-67.03	39.55
2370 MHz	-67.95	41.67
2375 MHz	-25.71	22.72
2380 MHz	-10.45	8.52
2385 MHz	-4.32	5.63
2390 MHz	-1.86	1.44

Typical series reference data

The N-K and SMA-K configurations share these typical series reference data.

Parameter	S12 (dB)	S11 VSWR
2450 MHz	-0.77	1.55

Mechanical and Interface Specifications

Parameter	Value
RF Connector	N-K
Connector Shell Material	304 stainless steel
RF Impedance	50 Ω
Surface Finish	Black baked paint
Body Length	300 mm
Body Width	72 mm
Housing height from flange underside	<55 mm
Length Between Outer Flange Edges	320 mm
Number of mounting slots	4
Mounting slot width	4.5 mm
Arc-centre spacing within one slot	10 mm
Slot-centre pitch, lengthwise	310 mm
Slot-centre pitch, crosswise	50 mm
Connector Center Spacing	34 mm
RF axis offset from the top edge in side view	10 mm

Handling and Installation

Both RF connectors are on the same end of the housing. Clean the product surface without immersing the product in cleaning fluid. For conditions in which the overall product temperature exceeds 125 °C, consult LCRF before ordering.

Document notice

Specifications are subject to revision. Before design release, confirm the current document revision and product-specific requirements with LCRF. The approved quotation and order documentation define the supplied configuration.