Band-stop Filter · 4840–4940 MHz

The passbands are DC–4820 MHz and 4960–7000 MHz at maximum 2.5 dB loss. A 300 × 70 mm body and four 4.5 mm through-holes define the mounting interface.

RF Performance

Parameter	Value
Stopband	4840–4940 MHz
Stopband Rejection	≥60 dB (4840–4940 MHz)
Lower Passband	DC–4820 MHz
Upper Passband	4960–7000 MHz
Passband Insertion Loss	≤2.5 dB (DC–4820 MHz; 4960–7000 MHz)
Passband VSWR	≤1.8 (DC–4820 MHz; 4960–7000 MHz)

Design Ratings

Parameter	Value
Power Handling	150 W (Guaranteed by design)

Typical Measurements

Parameter	S12 (dB)	S11 VSWR
4800 MHz	-0.68	1.37
4820 MHz	-2.29	1.19
4825 MHz	-12.356	9.28
4830 MHz	-31.654	16.77
4835 MHz	-55.35	33.47
4840 MHz	-80.54	49.53
4880 MHz	-69.43	41.47
4900 MHz	-74.21	32.02
4920 MHz	-67.88	42.04
4940 MHz	-72.78	38.14
4945 MHz	-50.36	28.36
4950 MHz	-27.64	18.43
4955 MHz	-9.76	6.88
4960 MHz	-2.38	1.38

Typical Measurements

Parameter	S12 (dB)	S11 VSWR
5000 MHz	-0.67	1.59

Mechanical and Interface Specifications

Parameter	Value
RF Connector	N-K
Connector Shell Material	304 stainless steel
RF Impedance	50 Ω
Surface Finish	Black baked paint
Body Length	300 mm
Body Width	70 mm
Overall Length Including Flanges	320 mm
Longitudinal Mounting Pitch	310 mm
Transverse Mounting Pitch	62 mm
Through-hole Diameter	4.5 mm
Connector Center Spacing	32 mm
Flange Thickness	3 mm
Connector Axis Distance Below Body Top	10.5 mm
Overall Height	<45 mm
Through-hole Count	4

Handling and Installation

Both RF connectors are on the same end of the housing. Clean the product surface without immersing the product in cleaning fluid. For conditions in which the overall product temperature exceeds 125 °C, consult LCRF before ordering.

Document notice

Specifications are subject to revision. Before design release, confirm the current document revision and product-specific requirements with LCRF. The approved quotation and order documentation define the supplied configuration.