Band-stop Filter · 4900–4960 MHz

DC–4850 MHz and 5010–8000 MHz are the passbands, with insertion loss limited to 2.5 dB. Power capacity is 10 W, guaranteed by design. The body measures 192 × 53.5 mm, with overall height strictly below 36 mm.

RF Performance

Parameter	Value
Stopband	4900–4960 MHz
Stopband Rejection	≥50 dB (4900–4960 MHz)
Lower Passband	DC–4850 MHz
Upper Passband	5010–8000 MHz
Passband Insertion Loss	≤2.5 dB (DC–4850 MHz; 5010–8000 MHz)
Passband VSWR	≤1.8 (DC–4850 MHz; 5010–8000 MHz)

Design Ratings

Parameter	Value
Power Handling	10 W (Guaranteed by design)

Typical Measurements

Parameter	S12 (dB)	S11 VSWR
4800 MHz	-0.51	1.44
4850 MHz	-2.24	1.28
4860 MHz	-5.07	4.29
4870 MHz	-12.14	9.76
4890 MHz	-44.31	13.37
4900 MHz	-79.32	33.75
4915 MHz	-66.71	48.36
4930 MHz	-70.08	35.41
4945 MHz	-55.73	38.78
4960 MHz	-62.64	26.85
4970 MHz	-44.77	12.48
4990 MHz	-9.86	8.36
5000 MHz	-4.08	4.47
5010 MHz	-2.11	1.32

Typical Measurements

Parameter	S12 (dB)	S11 VSWR
5050 MHz	-0.67	1.54

Mechanical and Interface Specifications

Parameter	Value
RF Connector	SMA-K
Connector Shell Material	304 stainless steel
RF Impedance	50 Ω
Surface Finish	Black baked paint
Body Length	192 mm
Body Width	53.5 mm
Overall Length Including Flanges	212 mm
Longitudinal Mounting Pitch	202 mm
Transverse Mounting Pitch	43.5 mm
Connector Center Spacing	23.5 mm
Flange Thickness	5 mm
Connector Axis Distance Below Body Top	8 mm
Overall Height	<36 mm
Through-hole Count	4
Through-hole Diameter	4.5 mm

Handling and Installation

Both RF connectors are on the same end of the housing. Clean the product surface without immersing the product in cleaning fluid. For conditions in which the overall product temperature exceeds 125 °C, consult LCRF before ordering.

Document notice

Specifications are subject to revision. Before design release, confirm the current document revision and product-specific requirements with LCRF. The approved quotation and order documentation define the supplied configuration.