Band-stop Filter · 824–849 MHz

The DC–794 MHz and 879–3500 MHz passbands have a maximum insertion loss of 2 dB. Power capacity of 50 W and operation at −10…+50 °C are guaranteed by design. The black baked-paint body measures 201 × 30 × 18 mm.

RF Performance

Parameter	Value
Stopband	824–849 MHz
Stopband Rejection	≥50 dB (824–849 MHz)
Lower Passband	DC–794 MHz
Upper Passband	879–3500 MHz
Passband Insertion Loss	≤2 dB (DC–794 MHz; 879–3500 MHz)
Passband VSWR	≤1.8 (DC–794 MHz; 879–3500 MHz)

Design Ratings

Parameter	Value
Power Handling	50 W (Guaranteed by design)
Operating Temperature	−10…+50 °C (Guaranteed by design)

Typical series reference data

Several connector configurations share these typical data. Separate measurements for each configuration are unconfirmed.

Parameter	S12 (dB)	S11 VSWR
750 MHz	-0.25	1.44
794 MHz	-1.81	1.25
804 MHz	-3.75	4.33
814 MHz	-11.44	13.35
824 MHz	-70.40	38.58
828 MHz	-76.94	37.16
830 MHz	-55.78	39.42
836 MHz	-62.98	40.73
840 MHz	-71.55	41.17
846 MHz	-60.05	34.97
849 MHz	-76.56	31.13
859 MHz	-10.87	14.04
869 MHz	-3.66	3.66

Typical series reference data

Several connector configurations share these typical data. Separate measurements for each configuration are unconfirmed.

Parameter	S12 (dB)	S11 VSWR
879 MHz	-1.72	1.18
925 MHz	-0.34	1.5

Mechanical and Interface Specifications

Parameter	Value
RF Connector	N-K
Connector Shell Material	304 stainless steel
RF Impedance	50 Ω
Surface Finish	Black baked paint
Body Length	201 mm
Body Width	30 mm
Body Height	18 mm
Longitudinal Mounting Pitch	195 mm
Transverse Mounting Pitch	24 mm
RF axis offset from the lower edge in side view	9 mm
Connector Axis Distance from Body Side	15 mm
Mounting Hole Count	4
Mounting Threads	M2.5
Thread Depth	6 mm

Handling and Installation

The two RF connectors are on opposite ends of the housing. Clean the product surface without immersing the product in cleaning fluid. For conditions in which the overall product temperature exceeds 125 °C, consult LCRF before ordering.

Document notice

Specifications are subject to revision. Before design release, confirm the current document revision and product-specific requirements with LCRF. The approved quotation and order documentation define the supplied configuration.