


2000–6000 MHz GaAs PIN RF Limiter Die

Insertion loss: 0.3 dB (typical) / 0.4 dB (maximum); Limiting level: 15 dBm (typical) / 16 dBm (maximum); Maximum pulsed input power: 43 dBm (maximum) ($\tau = 200\ \mu\text{s}$; $D = 20\%$). Die dimensions: $1.8 \times 1.5 \times 0.1\ \text{mm}$.



RF characteristics · TA = +25 °C

Parameter	Symbol	Minimum	Typical	Maximum	Value	Unit
Operating frequency	-	2000	-	6000	2000–6000	MHz
Insertion loss	-	-	0.3	0.4	-	dB
Input VSWR	-	-	1.4	-	-	-
Output VSWR	-	-	1.4	-	-	-
Limiting level	-	-	15	16	-	dBm
Maximum pulsed input power	-	-	-	43	$\tau = 200\ \mu\text{s}$; $D = 20\%$	dBm


Environmental specifications

Parameter	Symbol	Minimum	Typical	Maximum	Unit
Storage temperature	-	-65	-	150	°C
Operating temperature	-	-55	-	125	°C

Die dimensions

Parameter	Value	Unit
Die dimensions	$1.8 \times 1.5 \times 0.1$	mm

Mechanical Outline



All dimensions are in mm [in].

Bond-pad assignments

Pins	Symbol	Function	Notes
2	RF_in	RF input	50 Ω
5	RF_out	RF output	50 Ω
1, 3, 4, 6	GND	Ground pad for probe testing	-

Current publication record · 1.3 · 2026-10-27. Product description or editorial content updated. Replaces revision 1.2.

Die integration and bias sequencing

Input and output DC-blocking capacitors are integrated.

Mechanical reference scope


Source-based dimensional guide in mm. Partial information; not a complete fabrication or wire-bonding drawing.

Performance curves

Plots from the source datasheet. Read each figure with its stated operating conditions.

Input/output matching; Insertion loss.

Source-page annotation: TA=+25°C. The displayed source plot bodies, including curves and grid, are retained; only exterior axes and layout are reformatted. No measurement arrays or hidden states are reconstructed.



[Source](#)

Document notice

Specifications are subject to revision. Before design release, confirm the current document revision and product-specific requirements with LCRF. The approved quotation and order documentation define the supplied configuration.