5000–6000 MHz GaAs PIN RF Limiter Die

LCI-LIM-5000-6000 is a GaAs PIN limiter bare die for 5000–6000 MHz, designed to limit RF power ahead of power-sensitive components.



Insertion loss: 0.45 dB (typical) / 0.5 dB (maximum); Limiting level: 18.5 dBm (typical) / 19.5 dBm (maximum); Maximum pulsed input power: 49 dBm (maximum) (τ = 2 ms; D = 20%); Maximum pulsed input power: 50 dBm (maximum) (τ = 300 µs; D = 30%). Die dimensions: 2 × 1.2 × 0.1 mm.

RF characteristics

TA = +25 °C

Parameter	Symbol	Minimum	Typical	Maximum	Value	Unit
Operating frequency	-	5000	-	6000	-	MHz
Insertion loss	-	-	0.45	0.5	-	dB
Input VSWR	-	-	1.2	1.3	-	-
Output VSWR	-	-	1.2	1.3	-	-
Limiting level	-	-	18.5	19.5	-	dBm
Maximum pulsed input power	-	-	-	49	τ = 2 ms; D = 20%	dBm
Maximum pulsed input power	-	-	-	50	τ = 300 µs; D = 30%	dBm

Environmental specifications

Parameter	Symbol	Minimum	Typical	Maximum	Unit
Storage temperature	-	-65	-	150	°C
Operating temperature	-	-55	-	70	°C

Bond-pad assignments

Pins	Symbol	Function	Notes
2	RFin	RF input	50 Ω
5	RFout	RF output	50 Ω
1, 3, 4, 6	GND	Ground pad for probe testing	-

Die dimensions

Parameter	Value	Unit
Die dimensions	2 × 1.2 × 0.1	mm

Partial dimensional reference in mm. Fabrication and wire bonding require complete drawings.



2.000 × 1.200 × 0.100 mm
X, Y: ±0.100 mm
X → · Y ↑ · X, Y: mm

Current publication record · 1.6 · 2026-11-12. Product description or editorial content updated. Replaces revision 1.5.

Die integration and bias sequencing

RFout includes an integrated DC-blocking capacitor.

Performance curves

Each performance plot applies to its stated operating conditions.

Input/output matching; Insertion loss.

Figure notes: TA=+25°C. Readings are approximate.



Document notice

Specifications are subject to revision. Before design release, confirm the current document revision and product-specific requirements with LCRF. The approved quotation and order documentation define the supplied configuration.