
2000–5000 MHz GaAs MMIC Low-Noise Amplifier Die — NF 0.45 dB (typical); P1dB 14 dBm (typical)

LCI-LNA-2000-5000-NF0p45T-P1DB14T · 2000–5000 MHz · GaAs MMIC Low-Noise Amplifier Die.



The RF table specifies: NF 0.45 dB (typical); Small-signal gain 30 dB (typical); P1dB 14 dBm (typical). RF test conditions: TA = +25 °C; Vd = +5 V.

Single-supply operation.

Input and output DC-blocking capacitors are integrated.

The RF pads do not require external DC-blocking capacitors; add the specified supply filtering at VDD.

Die dimensions: 1.8 × 0.85 × 0.1 mm.

RF characteristics

TA = +25 °C; Vd = +5 V

Parameter	Symbol	Minimum	Typical	Maximum	Value	Unit
Operating frequency	f	2000	-	5000	-	MHz
Output 1 dB compression power	P1dB	-	14	-	-	dBm
Saturated output power	Psat	-	-	-	15	dBm
Small-signal gain	Gain	-	30	-	-	dB
Small-signal gain flatness	ΔGain	-	±0.3	-	-	dB
Noise figure	NF	-	0.45	-	-	dB
Input VSWR	VSWR-in	-	1.6	-	-	-
Output VSWR	VSWR-out	-	1.6	-	-	-

DC bias and current

TA = +25 °C

Parameter	Symbol	Minimum	Typical	Maximum	Unit
Operating voltage	Vd	-	5	-	V
Quiescent current	Id	-	0.045	-	A

Absolute limits

Absolute limits; these are not normal operating targets.

Parameter	Symbol	Minimum	Typical	Maximum	Unit
Maximum operating voltage	-	-	-	6	V
Maximum input power	-	-	-	6	dBm
Storage temperature	-	-65	-	150	°C
Maximum channel temperature	-	-	-	175	°C

Die dimensions

Parameter	Value	Unit
Die dimensions	1.8 × 0.85 × 0.1	mm
Plan-view outline tolerance	±50	µm

Bond-pad assignments

Pins	Symbol	mm
1	RFin	0.100 × 0.120
2	RFout	0.100 × 0.120
3	VDD	0.100 × 0.100
4, 5, 6, 7	GND	0.100 × 0.100

Current publication record · 1.7 · 2026-11-12. Product description or editorial content updated. Replaces revision 1.6.

Integration notes


Single-supply operation. Input and output DC-blocking capacitors are integrated. The RF pads do not require external DC-blocking capacitors; add the specified supply filtering at VDD.

Pad connection notes

The listed GND pads are test ground pads.

Mechanical Outline

Outline and dimensioned coordinates in mm. Use this drawing as a dimensional reference. Fabrication and wire bonding require complete drawings.




Performance curves

Each performance plot applies to its stated operating conditions.

Small-signal gain; Noise figure; Input matching; Output matching; P_1; Saturated output power.

Readings are approximate. Figure notes: Vd = 5 V; Pin = −40 dBm. The listed Pin is not a fixed drive level for the P_1 or P_Sat curves. P_1 values are not specified as 1 dB compression points.



Document notice

Specifications are subject to revision. Before design release, confirm the current document revision and product-specific requirements with LCRF. The approved quotation and order documentation define the supplied configuration.