
24000–40000 MHz GaAs MMIC Low-Noise Amplifier Die — NF 2.5 dB (typical)



LCI-LNA-24000-40000-NF2p5T · 24000–40000 MHz · GaAs MMIC Low-Noise Amplifier Die.

The RF table specifies: NF 2.5 dB (typical); Small-signal gain 23 dB (typical); P1dB ≥ 11 dBm. RF test conditions: TA = +25 °C; Vd = +5 V; Vg = 0 V.

Single-supply operation.

Input and output DC-blocking capacitors are integrated.

Vd: 4 ↔ 8

Die dimensions: 1.98 × 1.29 × 0.1 mm.

RF characteristics

TA = +25 °C; Vd = +5 V; Vg = 0 V

Parameter	Symbol	Minimum	Typical	Maximum	Unit
Operating frequency	f	24000	-	40000	MHz
Output 1 dB compression power	P1dB	11	-	-	dBm
Small-signal gain	Gain	-	23	-	dB
Small-signal gain flatness	ΔGain	-	±1	-	dB
Noise figure	NF	-	2.5	-	dB
Input VSWR	VSWR-in	-	1.3	-	-
Output VSWR	VSWR-out	-	1.3	-	-

DC bias and current

TA = +25 °C

Parameter	Symbol	Minimum	Typical	Maximum	Unit
Operating voltage	Vd	-	5	-	V
Quiescent current	Id	-	0.063	-	A

Absolute limits

Absolute limits; these are not normal operating targets.

Parameter	Symbol	Minimum	Typical	Maximum	Unit
Maximum operating voltage	-	-	-	6	V
Maximum input power	-	-	-	15	dBm
Storage temperature	-	-65	-	150	°C
Maximum channel temperature	-	-	-	175	°C

Die dimensions

Parameter	Value	Unit
Die dimensions	1.98 × 1.29 × 0.1	mm
Plan-view outline tolerance	±100	µm

Bond-pad assignments

Pins	Symbol	mm
2	RFin	0.100 × 0.100
6	RFout	0.100 × 0.100
4, 8	Vd	0.100 × 0.100
1, 3, 5, 7	GND	0.100 × 0.100

Current publication record · 1.7 · 2026-11-12. Product description or editorial content updated. Replaces revision 1.6.

Integration notes


Single-supply operation. Input and output DC-blocking capacitors are integrated. Vd: 4 ↔ 8

Pad connection notes

The listed GND pads are test ground pads. Vd: 4 ↔ 8

Mechanical Outline

Outline and dimensioned coordinates in mm. Use this drawing as a dimensional reference. Fabrication and wire bonding require complete drawings.




1.980 × 1.290 × 0.100 mm
X, Y: ±0.100 mm
X → · Y ↑ · X, Y: mm


Performance curves


Each performance plot applies to its stated operating conditions.


Gain (dB); NF (dB); VSWR_in; VSWR_out; P_1 (dBm).


Figure notes: Vd = 5 V; Pin = −30 dBm. Conditions apply to the indicated plots and their own legends. Read symbols and units as labeled on the axes.











Document notice

Specifications are subject to revision. Before design release, confirm the current document revision and product-specific requirements with LCRF. The approved quotation and order documentation define the supplied configuration.