30–600 MHz GaAs MMIC Low-Noise Amplifier Die

LCI-LNA-30-600-NF0p6T — 30–600 MHz GaAs MMIC Low-Noise Amplifier Die.

Noise figure: 0.6 dB (typical); Small-signal gain: 32.3 dB (typical); Input VSWR: 1.2 (typical). Die dimensions: 0.85 × 1.15 × 0.1 mm.



RF characteristics

TA = +25 °C; Vd = +4 V

Parameter	Symbol	Minimum	Typical	Maximum	Unit
Operating frequency	-	30	-	600	MHz
Small-signal gain	-	-	32.3	-	dB
Small-signal gain flatness	-	-	±0.3	-	dB
Input VSWR	-	-	1.2	-	-
Output VSWR	-	-	1.25	-	-
Noise figure	-	-	0.6	-	dB

DC bias and current

Parameter	Symbol	Minimum	Typical	Maximum	Value	Unit
Operating voltage	-	-	-	-	4 / 5	V
Operating current (Vd = +4 V)	-	-	-	-	0.075 (Vd = +4 V)	A
Operating current	-	-	-	-	0.105 (Vd = +5 V)	A

Absolute limits

Parameter	Symbol	Minimum	Typical	Maximum	Unit
Maximum operating voltage	-	-	-	5.5	V
Maximum input power	-	-	-	15	dBm

Environmental specifications

Parameter	Symbol	Minimum	Typical	Maximum	Unit
Storage temperature	-	-65	-	150	°C
Operating temperature	-	-55	-	125	°C

Die dimensions

Parameter	Value	Unit
Die dimensions	0.85 × 1.15 × 0.1	mm

Outline and dimensioned coordinates in mm. Use this drawing as a dimensional reference. Fabrication and wire bonding require complete drawings.



Current publication record · 1.8 · 2026-11-12. Product description or editorial content updated. Replaces revision 1.7.

Die integration and bias sequencing

An external RF choke and input/output DC-blocking capacitors are required.

Performance curves

Each performance plot applies to its stated operating conditions.

Gain; NF; P_1; VSWR; P_1; ISO.

Figure notes: TA = +25 °C. (3): Gain ≠ P_1 (dBm); (4): NF ≠ VSWR. (5): (VD = 4 V). Conditions apply to the indicated plots and their own legends. Use the axis labels to identify the plotted quantities. Read symbols and units as labeled on the axes.



Document notice

Specifications are subject to revision. Before design release, confirm the current document revision and product-specific requirements with LCRF. The approved quotation and order documentation define the supplied configuration.