
10800–13000 MHz GaN MMIC Power Amplifier Die

LCI-PA-10800-13000-PS45T is a GaN MMIC power amplifier supplied as bare die for 10800–13000 MHz. It supports CW and pulsed operation.

The RF table specifies: Saturated output power: 45 dBm (typical); Power gain: 21 dB (typical); Power-added efficiency: 38 % (typical). RF test conditions: TA = +25 °C; Vd = +28 V; Vg = -2.8 V. Die dimensions: 3.4 × 3.52 × 0.1 mm.



RF characteristics

TA = +25 °C; Vd = +28 V; Vg = -2.8 V

Parameter	Symbol	Minimum	Typical	Maximum	Unit
Operating frequency	f	10800	-	13000	MHz
Saturated output power	Psat	-	45	-	dBm
Power gain	Gp	-	21	-	dB
Power-gain flatness	ΔGp	-	±0.3	-	dB
Power-added efficiency	PAE	-	38	-	%

DC bias and current

TA = +25 °C

Parameter	Symbol	Minimum	Typical	Maximum	Unit
Drain voltage	Vd	24	28	30	V
Gate voltage	Vg	-3	-2.8	-2.4	V
Quiescent drain current	Id	-	1.3	-	A
Dynamic drain current	Idd	-	3.3	-	A
Dynamic gate current	Igg	-	-	2	mA

Absolute limits

Absolute limits; these are not normal operating targets.

Parameter	Symbol	Minimum	Typical	Maximum	Value	Unit
Maximum drain-source voltage	Vd	-	-	30	-	V
Minimum gate bias	Vg	-5	-	-	-	V
Maximum input power	Pin	-	-	28	-	dBm
Maximum channel temperature	Top	-	-	225	-	°C
Storage temperature	TSTG	-65	-	150	-	°C
Load mismatch survival	-	-	-	-	3:1	-

Die dimensions

Parameter	Value	Unit
Die dimensions	3.4 × 3.52 × 0.1	mm
Plan-view outline tolerance	±50 (Plan-view outline only; the source does not specify thickness tolerance.)	µm


Current publication record · 1.8 · 2026-11-12. Product description or editorial content updated. Replaces revision 1.7.

Die integration and bias sequencing

Apply gate bias before drain bias at power-up. At power-down, remove drain bias before gate bias. Use clean handling, ESD protection and a carrier with thermal expansion compatible with the SiC die.

Mechanical Outline

Outline and dimensioned coordinates in mm. Use this drawing as a dimensional reference. Fabrication and wire bonding require complete drawings.





Performance curves


Each performance plot applies to its stated operating conditions.


Continuous wave (CW) — Saturated output power; Power-added efficiency; Dynamic drain current; Power gain.


Figure notes: Vd=+28V; Vg=-2.8V. Pin = 25 dBm; Pout / PAE: Vg = −3 / −2.8 / −2.6 V. Conditions apply to the indicated plots and their own legends.














Document notice

Specifications are subject to revision. Before design release, confirm the current document revision and product-specific requirements with LCRF. The approved quotation and order documentation define the supplied configuration.