2000–2800 MHz GaN MMIC Power Amplifier Die

LCI-PA-2000-2800-PS41T is a GaN MMIC power amplifier supplied as bare die for 2000–2800 MHz. It supports CW and pulsed operation.

The RF table specifies: Saturated output power: 41 dBm (typical); Power gain: 24 dB (typical); Power-added efficiency: 56 % (typical). RF test conditions: TA = +25 °C; Vd = +28 V; Vg = -2.6 V; Pin = 17 dBm; τ = 100 µs; D = 10%. Die dimensions: 2.4 × 2.7 mm.



RF characteristics

TA = +25 °C; Vd = +28 V; Vg = -2.6 V; Pin = 17 dBm; τ = 100 µs; D = 10%

Parameter	Symbol	Minimum	Typical	Maximum	Unit
Operating frequency	f	2000	-	2800	MHz
Saturated output power	Psat	40.7	41	-	dBm
Power gain	Gp	23.7	24	-	dB
Power-gain flatness	ΔGp	-	-	1	dB
Power-added efficiency	PAE	54	56	-	%
Small-signal gain	S21	30	31	31.5	dB
Small-signal gain flatness	ΔS21	-	-	±0.7	dB
Input VSWR	VSWR(in)	-	1.8	2	-

DC bias and current

Vd = +28 V

Parameter	Symbol	Minimum	Typical	Maximum	Value	Unit
Drain voltage	Vd	-	28	-	-	V
Gate voltage	Vg	-	-2.6	-	-	V
Quiescent drain current	Id	-	-	-	0.45	A

Absolute limits

Absolute limits; these are not normal operating targets.

Parameter	Symbol	Minimum	Typical	Maximum	Unit
Maximum drain-source voltage	Vd	-	-	32	V
Minimum gate bias	Vg	-5	-	-	V
Maximum input power	Pin	-	-	20	dBm
Maximum channel temperature	Top	-	-	200	°C
Storage temperature	TSTG	-65	-	150	°C

Die dimensions

Parameter	Value	Unit
Plan-view die dimensions	2.4 × 2.7 (Thickness is not specified.)	mm
Plan-view outline tolerance	±100 (Plan-view outline only; the source does not specify thickness tolerance.)	µm

Current publication record · 1.6 · 2026-11-12. Product description or editorial content updated. Replaces revision 1.5.

Die integration and bias sequencing

Apply gate bias before drain bias at power-up. At power-down, remove drain bias before gate bias. Use clean handling, ESD protection and a carrier with thermal expansion compatible with the SiC die. Outline and dimensioned coordinates in mm. Use this drawing as a dimensional reference. Fabrication and wire bonding require complete drawings.

Bond-pad dimensions

RFin: 100 × 100 µm; Vg: 100 × 100 µm; Vd1: 120 × 120 µm; Vd2: 130 × 130 µm; Vd3: 160 × 150 µm; RFout: 110 × 120 µm.

Mechanical Outline



Performance curves

Read each figure with its stated operating conditions.

Pulsed — Saturated output power; Dynamic drain current; Power-added efficiency; Power gain.

Figure notes: TA=+25°C; Vd=+28V; Vg=-2.6V; Pin=17dBm. Readings are approximate. Pulse width = 100 µs; duty cycle = 10%.









Continuous wave (CW) — Saturated output power; Dynamic drain current; Power-added efficiency; Power gain.

Figure notes: TA=+25°C; Vd=+28V; Vg=-2.6V; Pin=17dBm. Readings are approximate.









Document notice

Specifications are subject to revision. Before design release, confirm the current document revision and product-specific requirements with LCRF. The approved quotation and order documentation define the supplied configuration.