2000–6000 MHz GaN Packaged Power Amplifier — PSAT 44.5 dBm (typical)

LCI-PA-2000-6000-PS44p5T · 2000–6000 MHz · GaN Packaged Power Amplifier.



The RF table specifies: PSAT 44.5 dBm (typical); Power gain 17.5 dB (typical); PAE 35 % (typical). RF test conditions: TA = +25 °C; VDS = +28 V; VGS ∈ [-3.2, -2.4] V; Pin = 27 dBm; CW.

CMW010B

Apply gate bias before drain bias. Remove drain bias before gate bias.

Vg: C = 10 µF

Vg: 1, 3

RFin: 2

Vd: 4, 6

RFout: 5

Package outline dimensions: 18.03 × 8.7 mm.

RF characteristics

TA = +25 °C; VDS = +28 V; VGS ∈ [-3.2, -2.4] V; Pin = 27 dBm; CW

Parameter	Symbol	Minimum	Typical	Maximum	Unit
Operating frequency	f	2000	-	6000	MHz
Saturated output power	-	44	44.5	-	dBm
Power gain	-	17	17.5	-	dB
Power-added efficiency	-	30	35	-	%
Power-gain flatness	-	-	-	1.5	dB

DC bias and current

Parameter	Symbol	Minimum	Typical	Maximum	Value	Unit
Drain voltage	-	-	-	-	28	V
Gate voltage	-	-	-	-	[-3.2, -2.4]	V

Absolute limits

Absolute limits; these are not normal operating targets.

Parameter	Symbol	Minimum	Typical	Maximum	Unit
Maximum drain-source voltage	-	-	-	32	V
Minimum gate bias	-	-5	-	-	V
Storage temperature	-	-65	-	150	°C
Maximum input power	-	-	-	30	dBm

Absolute limits

Absolute limits; these are not normal operating targets.

Parameter	Symbol	Minimum	Typical	Maximum	Unit
Maximum channel temperature	-	-	-	225	°C

Package outline dimensions

Parameter	Value	Unit
Package outline dimensions	18.03 × 8.7	mm
Terminal span	14.7	mm

Current publication record · 1.6 · 2026-11-12. Product description or editorial content updated. Replaces revision 1.5.

Integration notes

CMW010B Apply gate bias before drain bias. Remove drain bias before gate bias. Vg: C = 10 µF Vg: 1, 3 RFin: 2 Vd: 4, 6 RFout: 5

Mechanical Outline

Partial drawing showing confirmed dimensions in mm. Use the complete installation drawing for installation.



Performance curves

Each performance plot applies to its stated operating conditions.

Output power; Power-added efficiency; Drain current; Power gain.

Readings are approximate. Vd = +28 V; Vg = −2.8 V; Pin = 27 dBm; CW.









Document notice

Specifications are subject to revision. Before design release, confirm the current document revision and product-specific requirements with LCRF. The approved quotation and order documentation define the supplied configuration.