2700–3500 MHz GaN SPDT MMIC Switch Die — IL 0.7 dB (typical)

LCI-SW-2700-3500-SPDT · 2700–3500 MHz · GaN SPDT MMIC Switch Die.



The RF table specifies: Insertion loss 0.7 dB (typical); Isolation 41 dB (typical); P0.2dB 51 dBm (typical). RF test conditions: TA = +25 °C.

The RF ports do not require external DC-blocking capacitors.

V1 / V2: 100 pF; 10000 pF; 10 nF

Die dimensions: 2.3 × 3 × 0.1 mm.

V1 (V) = -28; V2 (V) = 0; RF = RFc ↔ RF1

V1 (V) = 0; V2 (V) = -28; RF = RFc ↔ RF2

RF characteristics

TA = +25 °C

Parameter	Symbol	Minimum	Typical	Maximum	Unit
Operating frequency	f	2700	-	3500	MHz
Insertion loss	-	-	0.7	-	dB
Isolation	-	-	41	43	dB
Input power at 0.2 dB compression	-	-	51	-	dBm
Input VSWR	-	-	1.2	-	-
Output VSWR	-	-	1.2	-	-
Switching time	-	-	20	-	ns

Control voltages

Parameter	Symbol	Minimum	Typical	Maximum	Value	Unit
Control voltages (V < 0)	-	-	-	-	-28	V
Control voltages (0 V)	-	-	-	-	0	V

Absolute limits

Absolute limits; these are not normal operating targets.

Parameter	Symbol	Minimum	Typical	Maximum	Unit
Maximum input power [1]	-	-	-	52	dBm
Storage temperature	-	-65	-	150	°C
Operating temperature	-	-55	-	85	°C
Minimum gate bias	-	-60	-	-	V

[1] D = 15%

Die dimensions

Parameter	Value	Unit
Die dimensions	2.3 × 3 × 0.1	mm
Plan-view outline tolerance	±100	µm


Current publication record · 1.6 · 2026-11-12. Product description or editorial content updated. Replaces revision 1.5.

Integration notes

The RF ports do not require external DC-blocking capacitors. V1 / V2: 100 pF; 10000 pF; 10 nF V1 (V) = -28; V2 (V) = 0; RF = RFc ↔ RF1 V1 (V) = 0; V2 (V) = -28; RF = RFc ↔ RF2

Mechanical Outline

Outline and dimensioned coordinates in mm. Use this drawing as a dimensional reference. Fabrication and wire bonding require complete drawings.





Performance curves


Each performance plot applies to its stated operating conditions.


Insertion loss; Isolation; Port matching.

Figure notes: TA=+25°C.









Document notice

Specifications are subject to revision. Before design release, confirm the current document revision and product-specific requirements with LCRF. The approved quotation and order documentation define the supplied configuration.