


30–6000 MHz 30 dB Low-Noise Amplifier

Wideband receive LNA with 1.2 dB typical noise figure and 85 mA typical current.



Electrical specifications

Parameter	Value	Unit	Notes
Operating frequency	30–6000	MHz	-
Gain	30	dB	Typical: 30 dB.
Noise figure	1.2	dB	Typical: 1.2 dB.
Saturated output power (Psat)	≤10	dBm	Saturated output (Psat), not P1dB or guaranteed linear output. Maximum: 10 dBm.
Input S11 (signed source value)	−10	dB	Negative S11 convention retained from source; not recast as positive return loss. Typical: -10 dB.
Supply voltage	5	VDC	Typical: 5 VDC.
Dynamic current	85	mA	Typical: 85 mA.

Absolute maximum ratings

Parameter	Value	Unit
Absolute maximum supply voltage	≤7 (Absolute maximum rating; continuous operation or performance at this limit is not established. Maximum: 7 VDC.)	VDC
Absolute maximum input power	≤12 (Absolute maximum rating; continuous operation or performance at this limit is not established. Maximum: 12 dBm.)	dBm
Operating temperature	−40–+70	°C
Storage temperature	−40–+85	°C


Interfaces and contacts

Parameter	Value	Unit
RF input connector	SMA-K female	-
RF output connector	SMA-K female	-
DC supply interface	Feed-through capacitor	-
Ground interface	Grounding metal sheet	-

Mechanical specifications

Parameter	Value	Unit
Body dimensions	36.2 × 24 × 10	mm
Mounting-hole center spacing	31.6 × 19.4	mm
Mounting holes	4 × Ø3 (Four through holes.)	mm

Mechanical Outline



All dimensions are in mm [in].

Document notice

Specifications are subject to revision. Before design release, confirm the current document revision and product-specific requirements with LCRF. The approved quotation and order documentation define the supplied configuration.