


8000–12000 MHz GaN RF Power Amplifier System, 200 W Typical

The GaN system covers 8000–12000 MHz with 200 W typical saturated output and 40 W typical output at 1 dB compression. Gain is 53 dB minimum with ± 1.5 dB typical gain flatness.



Electrical Specifications · +28.0VDC; 25°C; 50Ω

Parameter	Symbol	Minimum	Typical	Maximum	Unit
Operating frequency	BW	8000	-	12000	MHz
Output power at 1 dB compression	P-1dB	-	40	-	W
RF output power @ PSAT	PSAT	-	200	-	W
Power gain @ PSAT	Gp	53	-	-	dB
Power gain flatness @ PSAT	ΔGp	-	± 1.5	-	dB
Input return loss	S11	-	-15	-	dB
Harmonics at 200 W	H	-	-15	-	dBc
Spurious signals @ PSAT	Spur	-	-60	-	dBc
Input/output impedance	Impedance	-	50	-	Ω
Operating voltage	VDC	-	28	-	VDC
Power-added efficiency @ 200W	Eff	-	20	-	%
DC current @ 200W	IDD	-	36	-	A

Absolute Maximum Ratings

Parameter	Rating
RF input drive without damage	+10 dBm maximum
Load VSWR at Pout = 100 W	∞ ; All load phases and amplitudes; continuous
Thermal overload	85 °C → Shutdown (maximum)


Environmental Specifications · Design targets; project confirmation required

Parameter	Minimum	Typical	Maximum	Unit	Notes
Operating temperature	-20	-	50	°C	-
Storage temperature	-25	-	65	°C	Storage temperature
Relative humidity (non-condensing)	-	-	95	%	-

Mechanical Specifications

Parameter	Value	Unit
Dimensions	430 × 400 × 133 mm (maximum)	mm
Weight	15 kg (maximum)	kg
RF input connector	SMA, female	-
RF output connector	N-K	-
DC/control interface	Hybrid, D-Sub 7W2, male	-

Mechanical Outline



All dimensions are in mm [in].

DC and Control Interface

Pin #	Description	Specification
A1	A1 — Ground	Ground
A2	A2 — Positive supply	+28V
1	1 — Enable	TTL logic high (3.3 V); internally pulled low
2	2 — Ground	Ground
3	3 — Temperature sense output	750 ±20 mV @25 °C; 10 mV/°C
4	4 — Current sense output	100 mV/A
5	5 — Ground	Ground

Document notice

Specifications are subject to revision. Before design release, confirm the current document revision and product-specific requirements with LCRF. The approved quotation and order documentation define the supplied configuration.