


DC–4 GHz Electromechanical SPDT RF Switch, L29-K Interfaces

CW power handling is 3000 W over DC–1 GHz and 2500 W over 1–4 GHz. Drive mode is failsafe and switching time is ≤15 ms.



General specifications

Parameter	Value	Unit
Model number	LCSPDT-DC4000-L29	-
Switch type	SPDT	-
Frequency range	DC–4 (Minimum: 0 GHz. Maximum: 4 GHz.)	GHz
Drive mode	Failsafe	-
Control option	TTL	-
Impedance	50	Ω
Switching speed	≤15 (Maximum: 15 ms.)	ms
Switching life	2000000 cycles	-

Electrical specifications

Parameter	Value	Unit	Notes
Insertion loss — DC–1 GHz	≤0.3	dB	DC–1 GHz Maximum: 0.3 dB.
Isolation — DC–1 GHz	≥70	dB	DC–1 GHz Minimum: 70 dB.
VSWR — DC–1 GHz	≤1.3	-	DC–1 GHz Maximum: 1.3.
CW power handling — DC–1 GHz	3000	W	DC–1 GHz
Insertion loss — 1–4 GHz	≤0.5	dB	1–4 GHz Maximum: 0.5 dB.
Isolation — 1–4 GHz	≥60	dB	1–4 GHz Minimum: 60 dB.
VSWR — 1–4 GHz	≤1.5	-	1–4 GHz Maximum: 1.5.
CW power handling — 1–4 GHz	2500	W	1–4 GHz

Power configuration options

Parameter	Value	Unit
Failsafe current — 28 V	400 (Discrete voltage configuration; no continuous supply range inferred. 28 V)	mA

Optional TTL specifications

Parameter	Value	Unit
TTL low voltage	0–0.3 (Minimum: 0 V. Maximum: 0.3 V.)	V
TTL high voltage	3–5 (Minimum: 3 V. Maximum: 5 V.)	V
TTL current	5–10	mA

Integration guidance

Parameter	Value	Unit
Supply and ground connection	Connect VDC and GND before operation.	-


Environmental limits

Parameter	Value	Unit	Notes
Operating temperature	–25–+65	°C	Minimum: -25 °C. Maximum: 65 °C.
Storage temperature	–55–+85	°C	Minimum: -55 °C. Maximum: 85 °C.
Shock	50 G / 11 ms	-	Non-operating shock.
Vibration	10 G RMS / 20–2000 Hz	-	Operating vibration.

Mechanical specifications

Parameter	Value	Unit
RF connectors	L29-K	-
Control connector	Pins / D-Sub 9-pin male	-
Weight	400	g

Mechanical Outline



All dimensions are in mm [in].

Control interfaces

Parameter	Value	Unit	Notes
TTL contact — 1	VDC	-	1
TTL contact — 2	TTL	-	2
TTL contact — 3	GND	-	3
TTL contact — 4-9	NC	-	4-9

Switching states

Parameter	Value	Unit
Failsafe, power off	COM-1	-
TTL low path	RF1-COM	-
TTL high path	RF2-COM	-

Document notice

Specifications are subject to revision. Before design release, confirm the current document revision and product-specific requirements with LCRF. The approved quotation and order documentation define the supplied configuration.